

TECHNICAL DATA

MANUFACTURING PROCESS:	Tufted 5/32"
SURFACE COMPOSITION:	Cut Pile, Multi-colour Design
PILE MATERIAL	100%Durapropylene Heat Set High Twist construction
PILE WEIGHT:	Approx. +/- 850 g/m2
PILE HEIGHT:	Approx. +/- 6mm
TOTAL WEIGHT:	Approx. +/- 3.550 kg/m2.
TOTAL HEIGHT:	Approx. +/-8mm
PRIMARY BACKING:	100% Spun Bonded Polyester Lutradur™
SECONDARY BACKING	Heavy Flexible, impermeable Fullflex™ PVC
FLAMMABILITY:	BS 4790 when classified to BS 5287 Low radius effect of ignition
COLOURFASTNESS TO LIGHT:	Minimum rating of 6 when tested in accordance with BS 1006
COLOURFASTNESS TO SHAMPOO:	Minimum rating of 4 when tested in accordance with BS 1006
STATIC ELECTRICITY	Low builds up of Static Electricity, permanently less than 2.5kv
SIZES	40X60, 60X90, 90X120, 90X150, 120X180, 120X240t
ROLL WIDTHS / LENGTHS:	90/ 120/ 200cm including PVC border/ by length 1500cm
AREAS OF USE	Contract
DIMENSIONAL VARIATIONS	+/- 2%

**** APPLICATION:**

Contract Master is tufted cut pile multi-colour design contract entrance carpet that combines high styling with solid performance. Manufactured with 100% Advanced Generation Continuous Filament Solution Dyed Polypropylene, this carpet provides outstanding resistance to stain, static and bacteria.

**** SECONDARY BACKING:**

Contract Master is backed with heavy flexible impermeable Fullflex™ PVC. The backing is +/- 2mm in thickness. The PVC backing is impermeable and will not fray or rot and can be steam cleaned as often as required.

**** MAINTENANCE:**

The solution dyed fibre blend used has exceptional resistance to soiling and allows the use severe cleaning solutions such as bleach. Polypropylene is mould, mildew resistant, and will not support bacterial growth.