

TECHNICAL DATA

MANUFACTURING PROCESS:	Spun bonded multi Filament
MATERIAL	100% PVC
THICKNESS	Approx. +/- 18mm, +/- 15mm, +/- 12mm, +/- 9mm
BACKING	Heavy Flexible Backing
SECONDARY BACKING	Heavy, Flexible impermeable Fullflex PVC on 9 mm + 12 mm
FLAMMABILITY:	NFP 92-5L ² M3 (if requested)
COLOURS	25 colours
SIZES	120cm x6m Rolls, Special sizes on request
AREAS OF USE	Contract, intensive use for large and small contracts

**** FALL-THRU IS DURABLE:**

The web construction will meet the demands of heavy traffic and will work effectively for years. The construction of the product means that it naturally demonstrates excellent anti – fatigue properties and therefore the product is especially suited to areas in which repetitive work is undertaken.

**** FALL- THRU IS ECONOMICAL:**

Fall-Thru pays for itself many times over in the savings it offers in terms of cleaning cost and the protection of expensive floorcoverings.

**** FALL- THRU IS EASY TO INSTALL:**

Either free standing or in a mat well, it can be easily cut to size with a sharp knife. Edging kits are also available which allow the product to be used in areas, which do not feature a mat well.

**** FALL- THRU IS EASY TO CLEAN:**

Shaking or vacuuming removes dirt. From time to time it can be hosed or spray cleaned and will dry quickly.

**** PRODUCT RANGE:**

There are 5 different qualities of Fall-Thru, available in 25 different colours.

<u>PRODUCT DESCRIPTION</u>	<u>CODE</u>	<u>HEIGHT</u>	<u>WEIGHT (approx.)</u>	<u>FILAMENT</u>
> EXTRA DUTY PLUS	(EP)	18MM	7.30 kg	THICK Unbacked
> EXTRA DUTY	(ED)	15MM	5.30 kg	THICK Unbacked
> SCHMIDT FLOOR	(LM)	11MM	5.30 kg	THIN Backed
> SCHMIDT FLOOR	(LU)	11MM	2.80 kg	THIN Unbacked
> SCHMIDT MATTING	(SF)	9MM	4.50 kg	THIN Backed

MATTING SIZES: 40X60, 60X90, 90X120, 90X150, 120X180
ROLL SIZE IS 120 x 600 cm,