

## TECHNICAL DATA

<b>MANUFACTURING PROCESS:</b>	Tufted 5/32"
<b>SURFACE COMPOSITION:</b>	Cut Pile
<b>PILE MATERIAL</b>	100% Nylon PA6
<b>PILE WEIGHT:</b>	Approx. +/- 650 g/m2
<b>PILE HEIGHT:</b>	Approx. +/- 6mm
<b>TOTAL WEIGHT:</b>	Approx +/- 3.450 g/m2
<b>TOTAL HEIGHT:</b>	Approx. +/-7mm
<b>PRIMARY BACKING:</b>	100% Spun Bonded Polyester Lutradur
<b>SECONDARY BACKING</b>	Heavy Flexible, Impermeable Fullflex PVC
<b>SIZES:</b>	40X60, 60X90, 90X120, 90X150, 120X180, 120X240. Specials on request
<b>COLOURS</b>	Beige/Black stripe, Blue/Black stripe, Red/Black stripe, Anthracite/Black stripe
<b>AREAS OF USE</b>	Contract Low Traffic

### **\*\* APPLICATION:**

The specially created pattern effect creates an optical barrier that keeps the mat looking clean while it continues its job of collecting dirt. This quality makes it ideal for areas that might not be able to be cleaned every day like corridors and lift areas.

### **\*\* LAYING INSTRUCTIONS**

#### LOOSE

Mats covering small areas and runners can be easily laid loose due to heavy anti-slip PVC backing

### **\*\* SECONDARY BACKING:**

Omega is backed with heavy flexible impermeable Fullflex™ PVC. The backing is +/- 2mm in thickness. The PVC backing is impermeable and will not fray or rot and can be steam cleaned as often as required.

### **\*\* MAINTENANCE:**

Regular cleaning is essential to maintain the long -term performance of Omega. We recommend daily cleaning with a vacuum cleaner. Periodically the spray extraction cleaning method should be used.