

TECHNICAL DATA

MANUFACTURING PROCESS:	Tufted 5/32"
FIBRE:	100% B.C.F Heat Set Twisted Nylon 6
SURFACE COMPOSITION:	Tufted Cut Pile
PILE MATERIAL	
PILE WEIGHT:	Approx. +/- 750 g/m ²
PILE HEIGHT:	Approx. +/- 7mm
TOTAL WEIGHT:	Approx. +/- 2850 g/m ²
TOTAL HEIGHT:	Approx. +/- 8mm
PRIMARY BACKING:	100% Spunbonded Polyester Lutradur®
SECONDARY BACKING:	100% Nitrile Rubber Contoure moulded backing
FLAMMABILITY:	EN 13501 - (2002) Cf1 / S1
BACKING OPTIONS:	Gripper , perforated backing and labelling available.
STATIC ELECTRICITY:	Low
COLOURS:	To be selected from Schmidt Colour Selector Chart
SIZES:	60X85, 85x120, 85X150, 120X180.
AREAS OF USE:	Contract Medium Traffic
WASHING TEMPRATURE:	40 °C
DEMENSIONAL VARIATION:	+/- 2%

**** SECONDARY BACKING:**

100% Nitrile Rubber, Contour Moulded™ Oil / Chemical Resistant

**** MAINTENANCE:**

The product may be cleaned using a vacuum cleaner on a daily basis, periodically the spray extraction method can be used (temprature must not exceed 40°C). The host dry cleaning system may also be used. Machine Washing must not exceed 40°C, use only detergents witch contain no bleaching agent.