

TECHNICAL DATA

MANUFACTURING PROCESS:	Tufted 5/32"
SURFACE COMPOSITION:	Cut Pile, multi coloured design
PILE MATERIAL	Solution Dyed, Polyamide / Nylon
PILE WEIGHT:	Approx. +/- 750 g/m ²
PILE HEIGHT:	Approx. +/- 6mm
TOTAL WEIGHT:	Approx.+/- 2850 g/m ²
TOTAL HEIGHT:	Approx. +/- 8mm
PRIMARY BACKING:	100% Spun Bonded Polyester Lutradur™
SECONDARY BACKING	100% Nitrile Rubber, Contour Moulded™
FLAMMABILITY	EN 13501 - (2002) Cf1 / S1
ANTI STATIC BEHAVIOUR	Minimal Electrostatic charge only, Resistance 2,1 x 10 (11) Ohm, to DIN 54345
COLOURFASTNESS TO LIGHT:	Solution Dyed 10 year guarantee against colour loss/ fade
COLOURFASTNESS TO SHAMPOO:	Solution Dyed 10 year guarantee against colour loss/ fade
STATIC ELECTRICITY	Low builds up of Static Electricity, permanently less than 2.5kv
SIZES	40x60, 60x85, 85x120, 85x150, 115x180, 115x240
BACKING	Gripper, perforated backing and labelling available
WASHING TEMPERATURE	Max. 80 C
DIMENSIONAL VARIATIONS	+/- 2 %
ROLLS	150x250cms, widths up to 2metres, lengths up to 6metres

**** APPLICATION:**

Super Nytex is a washable mat and symbolises the exceptionally high standards required by the janitorial/rental industry. Schmidt International incorporates a unique special contour moulding process into their manufacturing which ensures that our mats have two unique advantages. Firstly, since the mat is slightly curved, it demonstrates suction properties which enable it to stay in place better on most floor surfaces. Secondly, contour moulding means that the rubber naturally goes to the edges of the mat thus reinforcing the edges which typically endure the maximum everyday's stresses.

100% solution dyed nylon is used, therefore offering the maximum durability. The fibres are also guaranteed for up to 10 years against colour fading, which is a vitally important factor when installations are undertaken, where the mat will be exposed to the elements and continual washing.

**** LAYING INSTRUCTIONS**

LOOSE

Mats covering small areas and runners can be easily laid loose due to heavy anti-slip PVC backing

**** SECONDARY BACKING:**

100% Nitrile Rubber, Contour Moulded™ Oil / Chemical Resistant

**** MAINTENANCE:**

ELIMINATES COLOUR LOSS PROBLEMS!!

1. Super Nytex carries a 10 year guarantee against colour loss
2. Colour fast to light, washing and, if stains, it can be bleached using approved techniques.
3. Anti-Static and will retain at least 90% of its pile fibre through its life
4. Different colours of Super Nytex can be washed together without cross staining
5. Low temperature washing removes all normal soiling. However, it can be processed at 80c without any staining or colour loss. do not wash with space dyed high twist nylon or cotton mats.