

TECHNICAL DATA

MANUFACTURING PROCESS:	Tufted 5/32"
SURFACE COMPOSITION:	Cut Pile, multi-colour design
PILE MATERIAL	100% Spun Polyamide (Nylon)
PILE WEIGHT:	Approx. 750 g/m2
PILE HEIGHT:	Approx. +/- 6mm
TOTAL WEIGHT:	Approx. +/- 3.550 g/m2.
TOTAL HEIGHT:	Approx. +/-8mm
PRIMARY BACKING:	100% Spun Bonded Polyester Lutradur™
SECONDARY BACKING	Heavy flexible Impermeable Fullflex™ PVC backing
FLAMMABILITY TEST:	BS 54332 / 66081
COLOURFASTNESS TO LIGHT:	Min. rating of 5
COLOURFASTNESS TO SHAMPOO:	Min. rating of 4
AREAS OF USE	Intensive, Contract,
COLOURS	Brown, Green, Blue, Red and Grey
SIZES	40x60, 60x90, 90x120, 90x150, 120x180, 120x240
ROLLS, WIDTH/ LENTGHS	90x1500, 120x1500 including PVC borders
DIMENSIONAL VARIATIONS	+/- 2%

**** APPLICATION:**

The specially created pattern effect creates an optical barrier that keeps the mat looking clean while it continues its job of collecting dirt. This quality makes it ideal for areas that might not be able to be cleaned every day like corridors and lift areas.

**** LAYING INSTRUCTIONS**

LOOSE

Mats covering small areas and runners can be easily laid loose due to heavy anti-slip PVC backing

FITTING ZONES

Large areas must be fitted and held down with glue suitable for soft PVC.

**** SECONDARY BACKING:**

Ultidecor is backed with heavy flexible impermeable Fullflex™ PVC. The backing is +/- 2mm in thickness. The PVC backing is impermeable and will not fray or rot and can be steam cleaned as often as required.

**** MAINTENANCE:**

Regular cleaning is essential to maintain the long -term performance of Ultidecor. We recommend daily cleaning with a vacuum cleaner. Periodically the spray extraction cleaning method should be used.