

TECHNICAL DATA

MANUFACTURING PROCESS:	Tufted 5/32"
SURFACE COMPOSITION:	Cut Pile multi colour design
PILE MATERIAL	100% Heat Set Twisted Polypropylene
PILE WEIGHT:	Approx. 750 g/m ²
PILE HEIGHT:	Approx. +/- 6mm
TOTAL WEIGHT:	Approx 3.550 g/m ² .
TOTAL HEIGHT:	+/- 7mm
PRIMARY BACKING:	100% Spun bonded Lutradur™ Polyester
SECONDARY BACKING	Fullflex™ Impermeable PVC flexible
FLAMMABILITY:	BS 4790 / DIN 4102
BURN BEHAVIOUR	DIN 54332 / 66081
AREAS OF USE	Commercial Medium Traffic
COLOURS	Brown/Black, Red/Black, Green/Black, Anthracite, Black/White, Brown/White, Navy/White, Blue/Black
SIZES	40X60, 60X90, 90X120, 90X150, 120X180, 120x240cms. Specials on Request
ROLLS	90x1500, 120x1500, 200x1500
DIMENSIONAL VARIATIONS	+/- 2%

**** APPLICATION:**

The specially created pattern effect creates an optical barrier that keeps the mat looking clean while it continues its job of collecting dirt. This quality makes it ideal for areas that might not be able to be cleaned every day like corridors and lift areas.

**** SECONDARY BACKING:**

LOOSE

Mats covering small areas and runners can be easily laid loose due to heavy anti-slip PVC backing

FITTING ZONES

Large areas must be fitted and held down with glue suitable for soft PVC.

**** SECONDARY BACKING:**

Ultitrend is backed with heavy flexible impermeable Fullflex™ PVC. The backing is +/- 2mm in thickness. The PVC backing is impermeable and will not fray or rot and can be steam cleaned as often as required.

**** MAINTENANCE:**

Regular cleaning is essential to maintain the long -term performance. We recommend daily cleaning with a vacuum cleaner. Periodically the spray extraction cleaning method should be used.